



19A Michelin str.
 CELL: 082 929 0057,
 FAX: 086 772 5040,

Vanderbijlpark
 TEL: 016 986 2194
 FAX: 016 986 1882

VAT No: 4250274646

CK: 2007/186867/23

Website: www.sleepwaparte.co.za

E-mail: sales@sleepwaparte.co.za

STANDARD AXLES LENGTHS - BRAKED

AXLE DESCRIPTION	LENGTH (MM)
2500KG, 50MM SQUARE, 6/139.7	1420
2500KG, 50MM SQUARE, 6/139.7	1550
2500KG, 50MM SQUARE, 6/139.7	1805
2500KG, 50MM SQUARE, 6/139.7	1900
2500KG, 50MM SQUARE, 6/139.7	2000
2500KG, 50MM SQUARE, 6/139.7	2100
2500KG, 50MM SQUARE, 6/139.7	2200
2500KG, 50MM SQUARE, 6/139.7	2300

1800KG, 50MM SQUARE 6/139.7	1550
1800KG, 50MM SQUARE 6/139.7	1800
1800KG, 50MM SQUARE 6/139.7	1900
1800KG, 50MM SQUARE 6/139.7	2000
1800KG, 50MM SQUARE 6/139.7	2100
1800KG, 50MM SQUARE 6/139.7	2200
1800KG, 50MM SQUARE 6/139.7	2300

AXLE DESCRIPTION	LENGTH (MM)
1600KG, 45MM SQUARE, 5/114.3	1420
1600KG, 45MM SQUARE, 5/114.3	1500
1600KG, 45MM SQUARE, 5/114.3	1550
1600KG, 45MM SQUARE, 5/114.3	1675
1600KG, 45MM SQUARE, 5/114.3	1805
1600KG, 45MM SQUARE, 5/114.3	1900
1600KG, 45MM SQUARE, 5/114.3	2000
1600KG, 45MM SQUARE, 5/114.3	2100
1600KG, 45MM SQUARE, 5/114.3	2200
1600KG, 45MM SQUARE, 5/114.3	2300

1600KG, 45MM SQUARE 6/139.7	1420
1600KG, 45MM SQUARE 6/139.7	1500
1600KG, 45MM SQUARE 6/139.7	1550
1600KG, 45MM SQUARE 6/139.7	1575
1600KG, 45MM SQUARE 6/139.7	1675
1600KG, 45MM SQUARE 6/139.7	1805
1600KG, 45MM SQUARE 6/139.7	1900
1600KG, 45MM SQUARE 6/139.7	2000
1600KG, 45MM SQUARE 6/139.7	2100
1600KG, 45MM SQUARE 6/139.7	2200
1600KG, 45MM SQUARE 6/139.7	2300



19A Michelin str.
CELL: 082 929 0057,
FAX: 086 772 5040,

Vanderbijlpark
TEL: 016 986 2194
FAX: 016 986 1882

VAT No: 4250274646

CK: 2007/186867/23

Website: www.sleepwaparte.co.za

E-mail: sales@sleepwaparte.co.za

STANDARD AXLES LENGTHS - UNBRAKED

AXLE DESCRIPTION	LENGTH (MM)
900KG, 40MM ROUND, 4/100	1170
900KG, 40MM ROUND, 4/100	1220
900KG, 40MM ROUND, 4/100	1250
900KG, 40MM ROUND, 4/100	1300
900KG, 40MM ROUND, 4/100	1330
900KG, 40MM ROUND, 4/100	1365
900KG, 40MM ROUND, 4/100	1420
900KG, 40MM ROUND, 4/100	1450
900KG, 40MM ROUND, 4/100	1500
900KG, 40MM ROUND, 4/100	1560
900KG, 40MM ROUND, 4/100	1600
900KG, 40MM ROUND, 4/100	1650
900KG, 40MM ROUND, 4/100	1675
900KG, 40MM ROUND, 4/100	1700
900KG, 40MM ROUND, 4/100	1750
900KG, 40MM ROUND, 4/100	1805
900KG, 40MM ROUND, 4/100	1850
900KG, 40MM ROUND, 4/100	1900
900KG, 40MM ROUND, 4/100	1950
900KG, 40MM ROUND, 4/100	2000
900KG, 40MM ROUND, 4/100	2100

AXLE DESCRIPTION	LENGTH (MM)
1600KG, 45MM SQUARE, 5/114.3	1420
1600KG, 45MM SQUARE, 5/114.3	1550
1600KG, 45MM SQUARE, 5/114.3	1675
1600KG, 45MM SQUARE, 5/114.3	1805
1600KG, 45MM SQUARE, 5/114.3	1900
1600KG, 45MM SQUARE, 5/114.3	2000
1600KG, 45MM SQUARE, 5/114.3	2100
1600KG, 45MM SQUARE, 5/114.3	2200
1600KG, 45MM SQUARE, 5/114.3	2300

1600KG, 45MM SQUARE 6/139.7	1420
1600KG, 45MM SQUARE 6/139.7	1500
1600KG, 45MM SQUARE 6/139.7	1550
1600KG, 45MM SQUARE 6/139.7	1575
1600KG, 45MM SQUARE 6/139.7	1675
1600KG, 45MM SQUARE 6/139.7	1805
1600KG, 45MM SQUARE 6/139.7	1900
1600KG, 45MM SQUARE 6/139.7	2000
1600KG, 45MM SQUARE 6/139.7	2100
1600KG, 45MM SQUARE 6/139.7	2200
1600KG, 45MM SQUARE 6/139.7	2300

2500KG, 50MM SQUARE, 6/139.7	1420
2500KG, 50MM SQUARE, 6/139.7	1550
2500KG, 50MM SQUARE, 6/139.7	1675
2500KG, 50MM SQUARE, 6/139.7	1805
2500KG, 50MM SQUARE, 6/139.7	1900
2500KG, 50MM SQUARE, 6/139.7	2000
2500KG, 50MM SQUARE, 6/139.7	2100
2500KG, 50MM SQUARE, 6/139.7	2200
2500KG, 50MM SQUARE, 6/139.7	2300

3000KG, 55MM SQUARE 5/165.1	1675
-----------------------------	------